



QP - 124R

24 Port Fast Ethernet Switch

10/100 Mbps
with 24 Ports

Description

24 Port 10/100Mbps switch supports the function of auto-negotiation and automatic crossing.
Compliant with IEEE802.3x standard for data flow control for full duplex mode.
Ideal for using at offices.
Easy Plug and Play installation.
Low Energy consumption.

Features

Compliant with the IEEE 802.3 10Base-T Ethernet, IEEE 802.3u 100Base-TX specifications.
24 port 10/100Mbps TX Auto-Negotiation Ethernet Switch.
Automatic Source MAC Address Learning and Aging.
IEEE 802.3x flow control for Full-duplex.
Back Pressure function for 10/100Mbps Half-duplex operation.

Specifications

Standard: IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3x Flow Control
Port: 24 10/100Mbps Auto-Negotiation RJ45 ports (Auto MDI/MDIX)
Network Media: 10BASE-T: UTP Cat.3 or up, 100BASE-TX: UTP Cat.5 or up.
Transmission Method: Store and Forward
Data Transfer Rate: 10/100M (Half-duplex), 10/100M (Full-duplex)

Access Method: CSMA/CD
LED Indicators: Power, Link/Act
Environment Operating
Temperature: 0°C~40°C
Storage Temperature: -40°C~70°C
Operating Humidity: 10%~90%RH(non-condensing)
Storage Humidity: 5%~90%RH(non-condensing)
Dimensions: 445mmx123mmx45mm
Safety & Emission: FCC, CE

